


■ 推力滚针和保持架组件

推力轴承垫圈



D _h /d	外形尺寸 (mm)					基本 额定动 载荷 C _r (N)	基本 额定静 载荷 C _{0r} (N)	极限转速 min ⁻¹	推力滚针和保持架组件		推力轴承垫圈	
	D _c /D	D _w	B ₁	E _b	E _a				型号	重量 (kg)	型号	重量 (kg)
4	14	2	1	5	13	4400	8000	21500	AX K0414-TN	0.0007	AS0414	0.001
5	15	2	1	6	14	4750	9200	20600	AX K0515-TN	0.0008	AS0515	0.001
6	19	2	1	7	18	6800	15500	18900	AX K0619-TN	0.001	AS0619	0.002
8	21	2	1	9	20	7800	19400	17800	AX K0821-TN	0.002	AS0821	0.002
10	24	2	1	12	23	9200	25500	16900	AX K1024	0.003	AS1024	0.003
12	26	2	1	14	25	9900	29000	15200	AX K1226	0.003	AS1226	0.003
15	28	2	1	17	27	11300	36000	13200	AX K1528	0.004	AS1528	0.003
17	30	2	1	19	29	11900	39500	12100	AX K1730	0.004	AS1730	0.004
20	35	2	1	22	34	13100	46500	10500	AX K2035	0.005	AS2035	0.005
25	42	2	1	29	41	14700	58000	8400	AX K2542	0.007	AS2542	0.007
30	47	2	1	34	46	16300	70000	7300	AX K3047	0.008	AS3047	0.008
35	52	2	1	39	51	17800	81000	6500	AX K3552	0.010	AS3552	0.009
40	60	3	1	45	58	28000	114000	5600	AX K4060	0.016	AS4060	0.012
45	65	3	1	50	63	30000	128000	5100	AX K4565	0.018	AS4565	0.013
50	70	3	1	55	68	32000	143000	4700	AX K5070	0.020	AS5070	0.014
55	78	3	1	60	76	38000	186000	4250	AX K5578	0.028	AS5578	0.018
60	85	3	1	65	83	44500	234000	3900	AX K6085	0.033	AS6085	0.022
65	90	3	1	70	88	46500	255000	3650	AX K6590	0.035	AS6590	0.024
70	95	4	1	74	93	54000	255000	3450	AX K7095	0.060	AS7095	0.025
75	100	4	1	79	98	55000	265000	3250	AX K75100	0.061	AS75100	0.027
80	105	4	1	84	103	56000	280000	3100	AX K80105	0.063	AS80105	0.028
85	110	4	1	89	108	58000	290000	2950	AX K85110	0.067	AS85110	0.029
90	120	4	1	94	118	73000	405000	2700	AX K90120	0.086	AS90120	0.039
100	135	4	1	105	133	91000	560000	2420	AX K100135	0.104	AS100135	0.050
110	145	4	1	115	143	97000	620000	2230	AX K110145	0.122	AS110145	0.055
120	155	4	1	125	153	102000	680000	2070	AX K120155	0.131	AS120155	0.059
130	170	5	1	136	167	135000	840000	1900	AX K130170	0.205	AS130170	0.065
140	180	5	1	146	177	138000	900000	1780	AX K140180	0.219	AS140180	0.079
150	190	5	1	156	187	143000	960000	1680	AX K150190	0.232	AS150190	0.084
160	200	5	1	166	197	148000	1020000	1590	AX K160200	0.246	AS160200	0.089